EPSON SureColor F-series driver

Supported printers

- EPSON SC-F6000 Series: 6000, 6070, 6080
- EPSON SC-F6200 Series: 6200, 6270, 6280
- EPSON SC-F6300 Series: 6300, 6370, 6380
- EPSON SC-F7000 Series: 7000, 7070, 7080
- EPSON SC-F7100 Series: 7100, 7170, 7180
- EPSON SC-F9200 Series: 9200, 9270, 9280

Specification summary

Item	SC-F6000/6200/6300	SC-F7000	SC-F7100	SC-F9200
Print head	360 nozzles x 10 lines x 1 TFP head.1 inch height. 720 nozzles/ink			Dual print head
Printer width	44 inch	64 inch		
Ink set	CMYK. 4C Aqueous dispersed Sublimation Dye Ink			High density black ink
Paper source	Roll paper (spindle-less). Sheet paper is not supported.			
Media size	Max. width: 1,118 mm (44”) Min. width: 254 mm Max. thickness: 0.5 mm	Max. width: 1,625 mm (64”) Min. width: 300 mm Max. thickness: 1.0 mm		
Interface	USB 2.0 10Base-T/100Base-T/1000Base-T			
Printer driver	Communication driver available			
Roll spindle	Spindle less, Spindle diameters: 2 and 3 inches			
Take-up reel	Available as an option	Standard equipment (up to 40 kg) Optional equipment (up to 80 kg)		
Cutting	Auto-rotary cutter	Manual cutting		
After heater	Not available		Standard equipment	

© 2022 Fiery, LLC. All rights reserved.

Item	SC-F6000/6200/6300	SC-F7000	SC-F7100	SC-F9200
Drying fan	Not available		Available as an option	

The SC-F60x0 is based on the EPSON SC-T Series platform (T-7000).



The SC-F7xx0 is based on the EPSON SC-S Series platform (SC-S306x0).



The SC-F92x0 is based on the EPSON SC-S Series platform (SC-S506x0)



Supported OS

- Windows 64Bit
- Mac OS X dropped with 7.0

Color mode

- CMYK

Print modes

Printer model	Printer resolution	Print mode
SC-F60x0, 62x0, 63x0 SC-F7x0 SC-F71x0	360 x 720 dpi	1 Pass
	720 x 720 dpi	2 Passes, 3 Passes, 4 Passes
	720 x 1440 dpi	6 Passes, 8 Passes
SC-F92x0	360 x 720 dpi	High Speed (1 Pass)
	720 x 720 dpi	High Speed (2 Passes) High Speed (3 Passes) High Speed (4 Passes) High Speed (4 Passes HQ) High Quality (3 Passes) High Quality (4 Passes) High Quality (4 Passes HQ)
	720 x 1440 dpi	High Speed (6 Passes) High Speed (8 Passes) High Quality (6 Passes) High Quality (8 Passes)

Supported options

Option	SC-F60x0/62x0/63x0	SC-F70x0	SC-F71x0	SC-F92x0
Print direction	Uni-directional/Bi-directional			
Dry time	0-100 minutes			
Auto-cut	On/Off	Not supported (manual cutting only)		
Roll paper tension	Use printer option	Use printer options		
	Standard	Off		
	High	0...40		

Option	SC-F60x0/62x0/63x0	SC-F70x0	SC-F71x0	SC-F92x0
	Higher		Automatic	
Roll paper tension check	Not supported	Use printer options		
		Off	On	
		On	Every page	
		Every page		
Heater	Not supported		Off	
			30-55°C (42°C default)	
			Use printer setting	
Blower	Not supported		Use printer options	
			Off	
			On	
Carriage Movement	Not supported	Use printer options		
		Data width		
		Printer width		
Feed after print	Not supported		Use printer options	
			Off	
			On (without back feed)	
Feed speed	Not supported	Use printer options	Use printer options	
		Standard	Standard	
		Low	Low	
			Automatic	
Media margin (Top)	0..255 mm			
Mirror	Printer driver horizontal mirror			
Wait for print completion	This checkmark controls the behavior after print data transfer: If enabled, the driver will wait until printer status becomes printed or error. Not F70x0/F92x0			